#### KOMET

## KUB Pentron® indexable drill Plain shank, 3×D, Ø DC m7: 43mm



### **Order data**

Order number	236615 43
GTIN	4047109276918
Item class	24P

## **Description**

#### **Version:**

- · Very high performance and long tool life thanks to optimised base body strength and special surface treatment.
- · Best dimensional accuracy under very difficult drilling conditions.
- · Stock costs reduced because internal and external inserts are identical.
- · Offset-axis drilling is possible up to  $V_{max} = 0.25$  mm. Maximum  $\emptyset = D + 0.5$  mm achievable by offsetting.

**Bore tolerance:**  $\emptyset D - 0.1 / + 0.2$ 

### **Application:**

· Under extreme machining conditions.

With indexable inserts No. 236605 – 236610.

## **Supplied with:**

Clamp screws (without indexable inserts).

#### Note:

Version 2×D and 3×D with ABS<sup>®</sup> also available on request in imperial sizes.

Version with PSC shank available on request.

# **Technical description**

Number of cutting edges Z	1
Shank length L <sub>s</sub>	68 mm
Reach L <sub>1</sub>	129 mm
ISO code indexable insert	SOGX 130508 46
Shank Ø D <sub>s</sub>	40 mm



Pack of insert screws	239652 20IP (6.3 Nm)
Series	KUB Pentron®
Nominal Ø D	43
Overhang L <sub>A</sub>	159 mm
Drill depth for indexable insert drill up to	3×D
Shank	ISO 9766
Use for drilling	limited centre drilling
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited drilling through a stack
Use for drilling	limited drilling with oblique exit
Use for drilling	limited cross-drilling
Through-coolant	yes
Machining strategy	HPC
Type of product	Indexable drill

# **Accessories**

Torque screwdriverwith scale, to take interchangeable blades maximum torque 1600 cNm	659906 1600
Torx Plus® insert screw set10 pieces Drive 20IP	239652 20IP
PrecisionBit for Torx Plus®, 1/4 inch E 6.3 Torx Plus® profile 20IP	674252 20IP
8 mm blade with magnetwith 1/4 inch bit holder overall length 50 mm	659874 50
Torque screwdriverwith scale, to take interchangeable blades maximum torque 1600 cNm	659957 1600