HOLEX

Machine reamer configurable, uncoated, Nominal Ø DC: 5mm

Order data

Order number	164180 5		
GTIN	4045197092175		
Item class	120		

Description

Version:

Reamers finish ground to match your specification.

Even number of teeth with irregular spacing. The hole is accurately round and free of chatter marks. The cylindrical ground land on the plain cutting section smooths the hole and guides the reamer. With Morse taper shank.

Application:

For reaming through holes, as the chips are evacuated in the cutting direction. Also suitable for blind holes due to the short chamfer lead.

Note:

For suitable reducing adapters for tools with MT shanks see **No. 343000-343530**. For **H7 fits** see No. 164000.

Technical description

Feed f in steel < 750 N/mm ²	0.1 mm/rev.		
Overhang L ₁	63 mm		
Nominal Ø D _c	5 mm		
Morse taper MT size	1		
Overall length L	133 mm		
Flute length L _c	23 mm		
Ø range	4.76 - 5.05 mm		
Number of cutting edges Z	6		
Reaming oversize in diameter	0.1 mm		

© Hoffmann GmbH Qualitätswerkzeuge

Coating	uncoated		
Tool material	HSS E		
Standard	DIN 208 B		
Helix angle	7-8 degrees		
Through-coolant	no		
Shank	Morse taper		
Application for type of drilling	for through hole		
Colour ring	without		
Type of product	Phillips bit		

User data

	Suitability	V _c	ISO code
Aluminium	suitable	20 m/min	Ν
Aluminium (short chipping)	suitable	20 m/min	Ν
Steel < 500 N/mm ²	suitable	15 m/min	Р
Steel < 750 N/mm²	suitable	10 m/min	Р
Steel < 900 N/mm ²	suitable	7 m/min	Р
Steel < 1100 N/mm ²	suitable	5 m/min	Р
Steel < 1400 N/mm ²	suitable only under restricted conditions	4 m/min	Ρ
INOX < 900 N/mm ²	suitable	5 m/min	М
INOX > 900 N/mm ²	suitable only under restricted conditions	5 m/min	М
Ti > 850 N/mm²	suitable only under restricted conditions	5 m/min	S
GG(G)	suitable only under restricted conditions	5 m/min	К
Cu	suitable only under restricted conditions	13 m/min	Ν
Oil	suitable		

wet maximum

suitable