

Garant
Solid carbide short stepped drill 90°, TiAlN, for threads: M16F

Order data

Order number	125050 M16F
GTIN	4045197265609
Item class	11E

Description
Version:

Very sturdy – step length to DIN 8378. Tight concentricity tolerances between drill and counterbore \varnothing guarantee exact alignment.

Application:

Particularly suitable for NC machines and automatic machines. For drilling tapping holes to DIN 336 sheet 1 with 90° countersinking. In the following operation, the tap therefore does not have to cut into the sharp edge of the hole.

Sizes **F: Tapping holes** for the following **fluteless taps**.

Technical description

for threads	M16F
$\varnothing D_2$ 2nd step with chamfer h8	18 mm
Flute length L_c	73 mm
Feed f in steel < 1100 N/mm ²	0.18 mm/rev.
$\varnothing D_1$ 1st step with chamfer h8	15.1 mm
Shank $\varnothing D_s$	18 mm
Overall length L	123 mm
No. of teeth Z	2
Through-coolant	no
Step height L_1 1st step	38.5 mm
Coating	TiAlN

Tool material	Solid carbide
Standard	DIN 8378
Type	N
Tolerance nominal \varnothing	h8
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Countersink angle	90 degrees
Shank tolerance	h6
Colour ring	without
Application for type of drilling	for blind hole and through hole
Type of product	Stepped drill

User data

	Suitability	V_c	ISO code
Alu plastics	suitable only under restricted conditions	260 m/min	N
Aluminium (short chipping)	suitable	180 m/min	N
Alu > 10% Si	suitable	180 m/min	N
Steel < 500 N/mm ²	suitable	90 m/min	P
Steel < 750 N/mm ²	suitable	90 m/min	P
Steel < 900 N/mm ²	suitable	90 m/min	P
Steel < 1100 N/mm ²	suitable	60 m/min	P
Steel < 1400 N/mm ²	suitable	35 m/min	P
INOX < 900 N/mm ²	suitable	35 m/min	M
INOX > 900 N/mm ²	suitable	30 m/min	M
Ti > 850 N/mm ²	suitable	25 m/min	S
GG(G)	suitable only under restricted conditions	110 m/min	K
CuZn	suitable	180 m/min	N

Uni	suitable
wet maximum	suitable
dry	suitable only under restricted conditions