



HOLEX Pro Steel solid carbide roughing end mill HPC, TiAlN, Ø DC: 6mm



Order data

Order number	203059 6
GTIN	4062406377076
Item class	12X

Description

Version:

For **roughing and finishing**.

Up to 0.5×D into solid material **at very high feed rates** with smooth cutting action. Extra-long version for avoiding interference contours.

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Technical description

Shank Ø D _s	6 mm
Tolerance nominal Ø	0 / -0.03
Direction of infeed	horizontal, oblique and vertical
Corner chamfer angle	45 degrees
Shank	DIN 6535 HA to h6
Feed f _z for side milling in steel < 900 N/mm ²	0.04 mm
Overall length L	65 mm
Recess Ø D ₁	5.5 mm
Flute length L _c	22 mm
No. of teeth Z	4
Corner chamfer width at 45°	0.1 mm
Feed f _z for slot milling in steel < 900 N/mm ²	0.03 mm

Overhang length L_1 incl. recess	29 mm
Cutting edge $\varnothing D_c$	6 mm
Helix angle	38 degrees
Series	Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End / face mill

User data

	Suitability	V_c	ISO code
Steel < 500 N/mm ²	suitable	200 m/min	P
Steel < 750 N/mm ²	suitable	190 m/min	P
Steel < 900 N/mm ²	suitable	140 m/min	P
Steel < 1100 N/mm ²	suitable	120 m/min	P
INOX < 900 N/mm ²	suitable only under restricted conditions	60 m/min	M
GG(G)	suitable	200 m/min	K
Uni	suitable		
wet maximum	suitable		

wet minimum	suitable only under restricted conditions
dry	suitable
Air	suitable
Services	
Shank grinding Type HB	129100 HB