

Machine tap Form B DIN 371, uncoated, M: M5



Order data

| Order number | 131150 M5 | | |
|--------------|---------------|--|--|
| GTIN | 4045197068989 | | |
| Item class | 11H | | |

Description

Version:

With spiral point.

Size M2.3 and M2.6 to old DIN profile. ISO 2 6H

HSS-E

Technical description

| Number of clamping slots | 3 | | |
|---------------------------|----------|--|--|
| Thread pitch | 0.8 mm | | |
| Number of cutting edges Z | 3 | | |
| Thread Ø | 5 mm | | |
| Tapping hole Ø | 4.2 mm | | |
| Standard | DIN 371 | | |
| Shank Ø D₅ | 6 mm | | |
| Overall length L | 70 mm | | |
| Shank square □ | 4.9 mm | | |
| Tolerance class | ISO 2 6H | | |
| Tool material | HSS E | | |
| Thread depth | 15 mm | | |
| Thread type | М | | |
| Thread size | M5 | | |

| Coating | uncoated | | |
|----------------------------------|--|--|--|
| Flank angle | 60 degrees | | |
| Thread standard | DIN 13 | | |
| Taper lead form | В | | |
| Shank | Plain shank with h9 | | |
| Through-coolant | no | | |
| Application for type of drilling | up to 3×D for through holes | | |
| Cutting direction | right-hand | | |
| Type of threading tool | Machine tap for conventional machining | | |
| Colour ring | without | | |
| Type of product | Тар | | |

User data

| | Suitability | \mathbf{V}_{c} | ISO code |
|-------------------------------|---|------------------|----------|
| Aluminium (short chipping) | suitable only under restricted conditions | 13 m/min | N |
| Steel < 500 N/mm ² | suitable | 15 m/min | Р |
| Steel < 750 N/mm ² | suitable | 15 m/min | Р |
| Oil | suitable | | |
| wet maximum | suitable only under restricted conditions | | |