

**Garant****Machine tap, uncoated, M: M3,5****Order data**

Order number	131700 M3,5
GTIN	4045197070036
Item class	11H

**Description****Version:****Sturdy design with 15° left-hand spiral.****Advantage:****Particularly suitable for interrupted cuts** (e.g. longitudinal groove in the hole).

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 0.6 mm

Overall length L: 56 mm

Shank  $\varnothing D_s$ : 4 mmShank square  $\square$ : 3 mmTapping hole  $\varnothing$ : 2.9 mm**Technical description**

Number of cutting edges Z	3
Number of clamping slots	3
Thread $\varnothing$	3.5 mm
Thread pitch	0.6 mm
Tapping hole $\varnothing$	2.9 mm
Standard	DIN 371
Shank $\varnothing D_s$	4 mm
Overall length L	56 mm

Shank square <input type="checkbox"/>	3 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	10.5 mm
Thread type	M
Thread size	M3.5
Coating	uncoated
Flank angle	60°
Thread standard	DIN 13
Taper lead form	D
Helix angle	15-20°
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap

## User data

	Suitability	V <sub>c</sub>	ISO code
Aluminium (short chipping)	suitable only under restricted conditions	13 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	15 m/min	P
Steel < 750 N/mm <sup>2</sup>	suitable	15 m/min	P
GG(G)	suitable only under restricted conditions	9 m/min	K
Oil	suitable		

wet maximum

---

suitable only under  
restricted conditions