



## Countersink 90°, TiN, External Ø Dc: 20,5 mm



### Order data

Order number	150180 20,5
GTIN	4045197085986
Item class	12M

### Description

#### Version:

**All countersinks have 3 cutting edges**, radially relieved.

Flutes are ground from solid.

Economy version, improved performance due to coating.

#### Application:

High precision countersinks for chatter-free countersinking.

Through-coolant: no

Number of cutting edges Z: 3

Number of cutting edges Z: 3

smallest countersink Ø for holes from: 3.5 mm

Overall length L: 63 mm

Shank Ø D<sub>s</sub>: 10 mm

for countersunk screws DIN 7991: M10

Feed f in steel < 500 N/mm<sup>2</sup>: 0.16 mm/rev.

### Technical description

External Ø	20.5 mm
Shank tolerance	h9
Feed f in steel < 500 N/mm <sup>2</sup>	0.16 mm/rev.
for countersunk screws DIN 7991	M10
smallest countersink Ø for holes from	3.5 mm
Shank Ø D <sub>s</sub>	10 mm

Overall length L	63 mm
Number of cutting edges Z	3
Coating	TiN
Countersink tip angle	90 degrees
Tool material	HSS
Standard	DIN 335 C
Shank	Plain shank with h9
Through-coolant	no
Colour ring	green
Type of product	Stepped drill and countersink