



Machine tap, TiN, UNC: 10-24



Order data

| | |
|--------------|---------------|
| Order number | 137865 10-24 |
| GTIN | 4045197533135 |
| Item class | 11H |

Description

Version:

Sturdy design, with 20° right-hand chip flutes. With special TiN coating, for stainless and acid-resistant steels. For use with **emulsion** (fat content minimum 8%).

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E

Norm: DIN 371

Threads per inch: 24

Thread Ø: 4.83 mm

Overall length L_{tot} : 70 mm

Shank Ø: 6 mm

Shank square: 4.9 mm

Tapping hole Ø: 3.9 mm

Technical description

| | |
|---------------------------|------------|
| Thread pitch | 1.058 mm |
| Threads per inch | 24 |
| Number of clamping slots | 3 |
| Number of cutting edges Z | 3 |
| Tapping hole Ø | 3.9 mm |
| Taper lead angle | 50 degrees |
| Thread Ø | 4.83 mm |

| | |
|----------------------------------|-----------------------------------|
| Norm | DIN 371 |
| Tool material | HSS E |
| Shank Ø | 6 mm |
| Overall length L _{tot} | 70 mm |
| Shank square | 4.9 mm |
| Thread depth | 9.66 mm |
| Thread type | UNC |
| Thread size | 10-24 |
| Coating | TiN |
| Flank angle | 60 degrees |
| Tolerance class | 2B |
| Taper lead form | C |
| Helix angle | 20 degrees |
| Schaft | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 2×D for blind holes |
| Cutting direction | right-hand |
| Type of threading tool | Machine tap for dynamic machining |
| Colour ring | blue |