

Garant
Solid carbide micro slot drill, DLC, $\varnothing D_c \times L_1$: 2X4mm

Order data

Order number	201141 2X4
GTIN	4062406387389
Item class	11X

Description
Version:

With **advanced DLC sp^2 coating**. For the **highest demands regarding performance and precision in aluminium materials**. **Extremely tight tolerances** ensure maximum accuracy. Double relief ground with 2 hollow-ground chamfers. **Recess angle $\alpha = 16^\circ$** .

Tolerances:

· **Neck \varnothing : $D_1 = 0 / -0.01$ mm.**

Extra-sturdy shank to reduce the tendency to vibrate.

Note:

At greater tool overhang lengths, use a reduced value for a_p !
 Values for:
 slots milled from solid: $a_p = 0.25 \times D \times a_{p,corr}$
 side milling: $a_p = 0.5 \times D \times a_{p,corr}$
To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!
 e.g: $vf = 18000$ [rpm] \times fz [mm/Z] \times z

Technical description

Corner chamfer angle	90 degrees
Overall length L	55 mm
Shank $\varnothing D_s$	6 mm
Overhang length L_1 incl. recess	4 mm
Cutting edge $\varnothing D_c$	2 mm
Correction factor $a_{p,corr}$	1
Shank	DIN 6535 HA to h5
No. of teeth Z	2

Flute length L_c	3 mm
Recess $\varnothing D_1$	1.91 mm
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal \varnothing	0 / -0.005
Helix angle	30 degrees
Feed f_z for slot milling in cast aluminium	0.033 mm
Feed f_z for side milling in cast aluminium	0.04 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.5 \times D$ for side milling
Through-coolant	no
Colour ring	yellow
Type of product	End / face mill

User data

	Suitability	V_c	ISO code
Aluminium	suitable	480 m/min	N
Aluminium (short chipping)	suitable	440 m/min	N
Alu > 10% Si	suitable	400 m/min	N
PMMA acrylic	Suitable	200 m/min	N
PE-HD	Suitable	160 m/min	N
PA 66	Suitable	200 m/min	N
PEEK	Suitable	150 m/min	N
PF 31	Suitable	130 m/min	N
PVDF GF20	suitable	180 m/min	N

POM GF25	Suitable	160 m/min	N
PA 66 GF30	suitable	150 m/min	N
PEEK GF30	suitable	130 m/min	N
PTFE CF25	suitable	160 m/min	N
Honeycomb sandwich	suitable only under restricted conditions	300 m/min	N
Cu	suitable	160 m/min	N
CuZn	suitable	200 m/min	N
wet maximum	suitable		
wet minimum	suitable		
dry	suitable only under restricted conditions		
Air	suitable		