Garant GREENPLUS

GARANT GreenPlus Clean & Weld, Contents (ml or l): 20



Order data

Order number	088003 20
GTIN	4062406403119
Item class	01L

Description

Version:

Premium 2-in-1 welding anti-spatter fluid Clean & Weld with cleaning function. Effectively prevents spatter from sticking when carrying out MIG/MAG welding and laser cutting. Thanks to its excellent wetting properties, can also be used as a cleaner before welding. 20-litre can. If necessary, please order the appropriate discharge valve (No. 088010 size 20-30). Clean & Weld is easy to apply and prevents weld spatters from sticking both when wet or dry, and protects workpieces, welding nozzles and welding accessories during the entire machining process. Contamination such as chips, machining oils, light corrosion protection oils or coolants can be easily and effectively cleaned using Clean & Weld before welding. The welding process can begin directly after on the clean surface. The contents contain form a barrier between the workpiece and the spatters, and provide temporary corrosion protection to all weldable metals. The sheet metal can easily be galvanised or painted immediately after the welding process. When laser cutting, Clean & Weld offers the benefit that the formation of slag is avoided at the penetration point of the laser and smoke residue can be removed more easily. No reworking of the cutting edges is necessary, thus saving valuable time.

- · Carries no hazard labels.
- · Can be used manually.
- · For refilling spray bottles and pressure sprayers.

Technical description

Boiling point	100 °C
Shape	liquid
Version	Can
Contents	20
Colour	blue
Storage temperature	2 - 40 °C
Sustainability	GARANT GreenPlus
pH value	8,5
Series	GreenPlus
Type of product	Separating agents

Accessories

GARANT GreenPlusCan discharge valve suitable for can size 20-30 l

088010 20-30