

Garant
Solid carbide roughing slot drill, uncoated, Ø d11 DC: 8 mm

Order data

Order number	205330 8
GTIN	4045197643995
Item class	11X

Description
Version:
Dimensions similar to DIN 6527.
Knuckle form profile.
Special profile for machining non-ferrous metals.

Through-coolant: no

Tolerance nominal Ø: d11

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

 Flute length L_c : 16 mm

 Overhang length L_1 incl. recess: 27 mm

 Recess Ø D_1 : 7.8 mm

Overall length L: 63 mm

 Shank Ø D_s : 8 mm

Technical description

Recess Ø D_1	7.8 mm
Feed f_z for side milling in short-chipping aluminium	0.08 mm
No. of teeth Z	3
Feed f_z for slot milling in short-chipping aluminium	0.06 mm
Overhang length L_1 incl. recess	27 mm
Corner chamfer width at 45°	0.45 mm

Cutting edge $\varnothing D_c$	8 mm
Shank $\varnothing D_s$	8 mm
Overall length L	63 mm
Flute length L_c	16 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	d11
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	WR
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------