

Garant

Solid carbide milling cutter MTC / TPC, TiAlN, Ø e8 DC: 20 mm



Order data

Order number	203082 20
GTIN	4045197538000
Item class	11X

Description

Version:

Specially ground with corner radii similar to torus cutters and **special coating** for best tool life and high metal removal rates. Dimensions to DIN 6527 long.

Application:

For milling **titanium** and **high temperature steels**.

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Tolerance nominal Ø: e8

No. of teeth Z: 5

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 5

Flute length L_c : 41 mm

Overhang length L_1 incl. recess: 52 mm

Recess Ø D_1 : 19.5 mm

Overall length L: 104 mm

Shank Ø D_s : 20 mm

Technical description

Overhang length L_1 incl. recess	52 mm
Recess Ø D_1	19.5 mm
No. of teeth Z	5
Feed f_z for side milling in titanium > 850 N/mm ²	0.08 mm

Cutting edge $\varnothing D_c$	20 mm
Shank $\varnothing D_s$	20 mm
Overall length L	104 mm
Flute length L_c	41 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	e8
Balance quality with shank	G 2.5 with HB
Helix angle	38 degrees
Corner rounding r_v	0.3 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.03 \times D$ for copy milling
Cutting width a_e for milling operation	$0.08 \times D$
Through-coolant	no
Machining strategy	MTC
Machining strategy	TPC
Colour ring	pink
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 20 mm	SZ2025 20

