

Burr GARANT Master Uni – medium, Carbide, Type: A1225



Order data Order number 540220 A1225 GTIN 4062406584795 Item class 51D

Description

Version:

The newly developed innovative tooth geometry permits a high metal removal rate and at the same time extremely smooth running and very good guidance. The optimum chip formation (no pointed chips) achieves high surface quality in roughing and finishing applications.

- · High rate of material removal.
- · Smooth running.
- Low thermal stress, long tool life, improved chip evacuation.
- \cdot For general-purpose use on steel, stainless steel, aluminium. Shank \varnothing 6 mm.

GARANT burrs are manufactured from high performance carbide grades with high wear-resistance and maximum cutting edge strength, using only the latest CNC machines. Steel shanks are used when the head diameter is larger than the shank diameter, otherwise they are made from solid carbide.

Application:

Suitable for use with power tools and industrial robots, on almost all materials. For deburring, edge breaking, cleaning,

weld and surface preparation.

Note:

Materials with poor heat conductivity: Reduce speed in order to avoid overheating the burr and smearing.

Technical description

Type of cut	Unequal toothing	
Overall length	65 mm	

Shape description	Cylindrical, without end cut		
Head ∅	12 mm		
Toothing grit designation	medium		
Shank Ø	6 mm		
Head length	25 mm		
Series	GARANT Master Uni		
Tool material	Carbide		
Type of product	Burr		

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu Mg	suitable only under restricted conditions		
Steel < 900 N/mm ²	Suitable		
Steel < 1400 N/mm ²	Suitable		
Steel < 55 HRC	Suitable		
Steel < 60 HRC	Suitable		
INOX	Suitable		
Ti	Suitable		
GG(G)	Suitable		
Uni	Suitable		