

## Garant

### Solid carbide torus cutter, uncoated, $\varnothing$ h6 DC / R1: 5/0,5mm



## Order data

Order number	206190 5/0,5
GTIN	4045197591661
Item class	11X

## Description

### Version:

**Eccentric relief ground**, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

Tolerances:

- **Corner radius**

$R_1 = 0.5$  tolerance  $\pm 0.02$ .

$R_1 > 0.5 - 1.5$  tolerance  $\pm 0.03$ .

$R_1 > 1.5$  tolerance  $\pm 0.05$ .

## Technical description

Cutting edge $\varnothing D_c$	5 mm
Feed $f_z$ for side milling in short-chipping aluminium	0.02 mm
No. of teeth Z	3
Overhang length $L_1$ incl. recess	19 mm
Feed $f_z$ for copy milling in short-chipping aluminium	0.02 mm
Recess $\varnothing D_1$	4.7 mm
Corner radius $R_1$	0.5 mm
Shank $\varnothing D_s$	6 mm
Flute length $L_c$	13 mm
Overall length L	57 mm
Balance quality with shank	G 2.5 with HA

Shank	DIN 6535 HA to h6
Helix angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Type	W
Tolerance nominal $\varnothing$	h6
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Cutting width $a_e$ for milling operation	0.5×D for side milling
Through-coolant	no
Shank tolerance	h6
Colour ring	yellow
Type of product	Torus cutter

## User data

	Suitability	$V_c$	ISO code
Aluminium	Suitable	180 m/min	N
Aluminium (short chipping)	suitable	140 m/min	N
Alu > 10% Si	suitable	105 m/min	N
PMMA acrylic	Suitable	180 m/min	N
PE-HD	Suitable	130 m/min	N
PA 66	Suitable	150 m/min	N
PEEK	Suitable	130 m/min	N
PF 31	Suitable	110 m/min	N
Cu	Suitable	80 m/min	N
CuZn	Suitable	100 m/min	N
wet maximum	suitable		

wet minimum	Suitable only under restricted conditions
dry	suitable only under restricted conditions
Air	suitable only under restricted conditions
<b>Services</b>	
Shank grinding Type HB	129100 HB