# Garant

HiPer-Drill cutter insert n7, HU7810, Ø D: 33-Xmm



## Order data

| Order number | 231630 33-X   |  |  |
|--------------|---------------|--|--|
| GTIN         | 4062406635831 |  |  |
| Item class   | 20N           |  |  |

### Description

#### Version:

Vee ground cutter inserts for precise positioning and stable seating.

Concentricity when assembled  $\leq$  20  $\mu$ m. For holes up to IT9 accuracy.

Note:

Cutting data applies for the base body  $5 \times D$ .

Drill pilot holes exclusively with cutter insert of the same type. Delivery time: 10 working weeks Minimum order quantity: 3 pieces

Items made to order for a specific customer:

Cancellation only up to a maximum of 3 working days after receipt of order acknowledgement. Items cannot be returned.

## **Technical description**

| Feed f in aluminium short-chipping | 0.54 mm/rev. |
|------------------------------------|--------------|
| Coating                            | uncoated     |
| Number of changes/inserts          | 1            |
| Series                             | HiPer-Drill  |

| for base body size        | 33 mm                    |  |  |
|---------------------------|--------------------------|--|--|
| Ø range                   | 33 - 33.99 mm            |  |  |
| Point angle               | 135 degrees              |  |  |
| Grade                     | HU7810                   |  |  |
| Tool material             | Carbide                  |  |  |
| Semi-Standard             | yes                      |  |  |
| Number of cutting edges Z | 2                        |  |  |
| Type of product           | Cutter insert for boring |  |  |

## User data

|                               | Suitability | V <sub>c</sub> | ISO code |
|-------------------------------|-------------|----------------|----------|
| Alu plastics                  | suitable    | 250 m/min      | Ν        |
| Aluminium (short<br>chipping) | suitable    | 200 m/min      | Ν        |
| Alu > 10% Si                  | suitable    | 150 m/min      | Ν        |
| CuZn                          | suitable    | 180 m/min      | Ν        |
| wet maximum                   | suitable    |                |          |