

**Re-Bo**
**Circular saw blade fine, Ø×thickness: 400X3,5mm**


## Order data

Order number	177000 400X3,5
GTIN	4045197245014
Item class	17B

## Description

### Version:

**German top quality product.** Precision tooth geometry and very fine ground side faces. Significant increase in service life and protection against edge build-up due to the **nitrided surface**.

### Application:

For low speed machines (approx. 50 rpm).

**Pitch t:** (tooth form).

- **4 mm (BW) – For profiles and pipes with 1.0 – 1.5 mm wall thickness.**
- **5 / 6 mm (HZ) – For medium profiles, pipes and solid bar with 1.5 – 20 mm wall thickness / cross-section.**
- **7 / 8 mm (HZ) – For thick profiles and solid bar up to approx. 50 mm wall thickness / cross-section.**
- **10 – 16 mm (HZ) – For extra thick cross-sections and solid bar more than 50 mm.**

### Note:

- **For stainless steels (such as V2A) the correct cutting speed and lubrication is crucial (see information in the machining handbook No. 110020).**
- **The concentricity and axial run-out values are considerably better than those to DIN 1840, in some cases by up to 50 %.**

## Technical description

Pitch t	8 mm
suitable for saw makes	Eisele
Bore Ø	40 mm
Thickness	3.5 mm
Ø	400 mm
No. of teeth Z	160
Drive hole Ø	11 mm
Number of drive holes	2
Drive hole pitch circle	65 mm
Tool material	HSS
Through-coolant	no
Type of product	Circular saw blade

## User data

	Suitability	V <sub>c</sub>	ISO code
Aluminium (short chipping)	suitable only under restricted conditions	800 m/min	N
Alu > 10% Si	suitable only under restricted conditions	600 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	37 m/min	P
Steel < 750 N/mm <sup>2</sup>	suitable	22 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable	20 m/min	P
Steel < 1100 N/mm <sup>2</sup>	suitable only under restricted conditions	15 m/min	P
INOX < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	11 m/min	M
INOX > 900 N/mm <sup>2</sup>	suitable only under restricted conditions	11 m/min	M

Ti > 850 N/mm <sup>2</sup>	suitable only under restricted conditions	15 m/min	S
GG(G)	suitable	27 m/min	K
CuZn	suitable only under restricted conditions	400 m/min	N
Uni	suitable		
wet maximum	suitable		
dry	suitable only under restricted conditions		
Air	suitable only under restricted conditions		