


**Circular saw blade fine, Ø×thickness: 250X2mm**

**Order data**

Order number	177050 250X2
GTIN	4045197700469
Item class	12T

**Description**
**Version:**

Precise format and good quality for a competitive price. **Vaporised surface** protects against edge build-up.

**Application:**

For low speed machines (approx. 50 rpm).

**Pitch t:** (tooth form).

- **4 mm (BW) – For profiles and pipes with 1.0 – 1.5 mm wall thickness.**
- **5 / 6 mm (HZ) – For medium profiles, pipes and solid bar with 1.5 – 20 mm wall thickness / cross-section.**
- **7 / 8 mm (HZ) – For thick profiles and solid bar up to approx. 50 mm wall thickness / cross-section.**
- **10 – 16 mm (HZ) – For extra thick cross-sections and solid bar more than 50 mm.**

**Note:**

- **For stainless steels (such as V2A) the correct cutting speed and lubrication is crucial (see information in the machining handbook No. 110020).**
- **The concentricity and axial run-out values are considerably better than those to DIN 1840, in some cases by up to 50 %.**

Tool material: HSS

Thickness: 2 mm

Bore Ø: 40 mm  
 No. of teeth Z: 200  
 Pitch t: 4 mm  
 Number of drive holes: 2; 4  
 Drive hole Ø: 8; 12 mm

## Technical description

Bore Ø	40 mm
suitable for saw makes	Eisele
Thickness	2 mm
Ø	250 mm
Pitch t	4 mm
No. of teeth Z	200
Number of drive holes	2; 4
Drive hole pitch circle	55; 64 mm
Drive hole Ø	8; 12 mm
Tool material	HSS
Through-coolant	no
Type of product	Circular saw blade

## User data

	Suitability	V <sub>c</sub>	ISO code
Aluminium (short chipping)	suitable only under restricted conditions	800 m/min	N
Alu > 10% Si	suitable only under restricted conditions	600 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	37 m/min	P
Steel < 750 N/mm <sup>2</sup>	suitable	22 m/min	P
Steel < 900 N/mm <sup>2</sup>	suitable only under restricted conditions	20 m/min	P
GG(G)	suitable	27 m/min	K

CuZn	suitable only under restricted conditions	400 m/min	N
Uni	suitable		
wet maximum	suitable		
dry	suitable only under restricted conditions		
Air	suitable only under restricted conditions		