

GARANT Master Titan solid carbide high-performance reamer HPC through hole, TiAlN, Nominal Ø DC: 8mm



Order data

Order number	1644108		
GTIN	4062406698195		
Item class	10P		

Description

Version:

Special HPC reamers of the latest generation, for **machining titanium**, with improved tooth geometry and further developed carbide substrate. Extra-short cutting edge for increased cutting performance values. Optimised cooling strategy with radially arranged coolant outlets aligned directly to the teeth.

Version suitable for NC with straight shank dia. for standard arbors especially in **hydraulic chucks** or **high precision collet chucks.** Very high concentricity and process reliability thanks to unequal spacing of the teeth and special profile of the round chamfer width.

Tolerance specifications:

Configurable: Reamers finish ground to match your specification.

Application:

Special version for through holes.

Note:

Delivery time: 4 weeks.

Technical description

Overhang L ₁	64 mm		
Ø range	7.701 - 8.2 mm		
Series	Master Titan		
Feed f in titanium > 850 N/mm ²	0.36 mm/rev.		
Shank Ø D _s	8 mm		
Nominal Ø D _c	8 mm		



Number of cutting edges Z	6		
Flute length L _c	10 mm		
Overall length L	100 mm		
Tolerance	Configurable		
Reaming oversize in diameter	0.1 mm		
Coating	TiAIN		
Tool material	HSS		
Standard	Manufacturer's standard		
Through-coolant	yes, with 25 bar		
Shank	DIN 6535 HA with h6		
Machining strategy	HPC		
Application for type of drilling	for through holes		
Colour ring	green		
Type of product	Reaming tool with non- detachable cutters		

User data

	Suitability	\mathbf{V}_{c}	ISO code
Ti > 850 N/mm ²	suitable		
wet maximum	suitable		