

# GARANT Master Titan solid carbide high-performance reamer HPC through hole, TiAlN, Nominal Ø DC: 14mm



### **Order data**

| Order number | 164410 14     |  |  |
|--------------|---------------|--|--|
| GTIN         | 4062406698294 |  |  |
| Item class   | 10P           |  |  |

## **Description**

#### **Version:**

**Special HPC reamers** of the latest generation, for **machining titanium**, with improved tooth geometry and further developed carbide substrate. Extra-short cutting edge for increased cutting performance values. Optimised cooling strategy with radially arranged coolant outlets aligned directly to the teeth.

**Version suitable for NC** with straight shank dia. for standard arbors especially in **hydraulic chucks** or **high precision collet chucks.** Very high concentricity and process reliability thanks to unequal spacing of the teeth and special profile of the round chamfer width.

#### **Tolerance specifications:**

**Configurable**: Reamers finish ground to match your specification.

#### **Application:**

Special version for through holes.

#### Note:

Delivery time: 4 weeks.

# **Technical description**

| Series                      | Master Titan |  |  |
|-----------------------------|--------------|--|--|
| Number of cutting edges Z   | 6            |  |  |
| Tolerance                   | Configurable |  |  |
| Flute length L <sub>c</sub> | 15 mm        |  |  |
| Nominal Ø D <sub>c</sub>    | 14 mm        |  |  |
| Overall length L            | 130 mm       |  |  |

| Ø range                                    | 13.201 - 14.2 mm                             |  |  |
|--|--|--|--|
| Feed f in titanium > 850 N/mm <sup>2</sup> | 0.48 mm/rev.                                 |  |  |
| Shank Ø D <sub>s</sub>                     | 14 mm  |  |  |
| Overhang L <sub>1</sub>                    | 85 mm  |  |  |
| Reaming oversize in diameter               | 0.1 mm                                       |  |  |
| Coating                                    | TiAIN  |  |  |
| Tool material                              | HSS  |  |  |
| Standard                                   | Manufacturer's standard                      |  |  |
| Through-coolant                            | yes, with 25 bar                             |  |  |
| Shank                                      | DIN 6535 HA with h6                          |  |  |
| Machining strategy                         | HPC  |  |  |
| Application for type of drilling           | for through holes                            |  |  |
| Colour ring                                | green  |  |  |
| Type of product                            | Reaming tool with non-<br>detachable cutters |  |  |

# **User data**

|                            | Suitability | <b>V</b> <sub>c</sub> | ISO code |
|----------------------------|-------------|-----------------------|----------|
| Ti > 850 N/mm <sup>2</sup> | suitable    |                       |          |
| wet maximum                | suitable    |                       |          |