Garant

GARANT Master Titan solid carbide high-performance reamer HPC blind hole, TiAIN, Nominal Ø DC: 4,5mm



Order data

| Order number | 164415 4,5 | | |
|--------------|---------------|--|--|
| GTIN | 4062406698379 | | |
| Item class | 10P | | |

Description

Version:

Special HPC reamers of the latest generation, for **machining titanium**, with improved tooth geometry and further developed carbide substrate. Extra-short cutting edge for increased cutting performance values. Optimised cooling strategy with radially arranged coolant outlets aligned directly to the teeth.

Version suitable for NC with straight shank dia. for standard arbors especially in **hydraulic chucks** or **high precision collet chucks.** Very high concentricity and process reliability thanks to unequal spacing of the teeth and special profile of the round chamfer width.

Tolerance specifications:

Configurable: Reamers finish ground to match your specification.

Application:

Special version for blind holes. **Note:** Delivery time: 4 weeks.

Technical description

| Nominal Ø D _c | 4.5 mm | | |
|--|--------------|--|--|
| Flute length L_c | 8 mm | | |
| Tolerance | Configurable | | |
| Overall length L | 75 mm | | |
| Feed f in titanium > 850 N/mm ² | 0.24 mm/rev. | | |

| Series | Master Titan | | |
|----------------------------------|--|--|--|
| Overhang L ₁ | 39 mm | | |
| Ø range | 4.201 - 4.7 mm | | |
| Number of cutting edges Z | 4 | | |
| Shank Ø D _s | 6 mm | | |
| Reaming oversize in diameter | 0.1 mm | | |
| Coating | TiAIN | | |
| Tool material | Solid carbide | | |
| Standard | Manufacturer's standard | | |
| Through-coolant | yes, with 25 bar | | |
| Shank | DIN 6535 HA with h6 | | |
| Machining strategy | HPC | | |
| Application for type of drilling | for through holes | | |
| Colour ring | green | | |
| Type of product | Reaming tool with non- detachable cutters | | |

User data

| | Suitability | V _c | ISO code |
|----------------------------|-------------|----------------|----------|
| Ti > 850 N/mm ² | suitable | | |
| wet maximum | suitable | | |