Garant

Solid carbide side milling cutter HPC, TiAlN, $\emptyset \times$ width ± 0.1×k11: 50X3 mm



Order data

Order number	185010 50X3
GTIN	4045197366962
Item class	11V

Description

Version:

Precision solid carbide side milling cutters in the HPC machining range.

Use as a set: Cutters with the same Ø and same number of teeth can be combined as a set and adjusted to the required width. Since the cutters have no raised bore collar, the staggered teeth mesh with each other.

2-piece sets are particularly economical. By reversing the side milling cutters, both side edges of each cutter can be used.

Note:

- Do not clamp the cutters in a set without a sufficiently thick arbor spacer ring, otherwise the cutters will be damaged.
- See Group 30 for suitable arbor spacer rings.

• Slots milled from solid: f_z for $a_e = 0.1 \times D$.

Bore \emptyset H6 d₁: 16 mm No. of teeth Z: 14 Collar thickness b ±0.1: 1.9 mm Collar \emptyset d₂ ±1: 34 mm Tooth height Zh: 8 mm Capability of combining 2 cutters of the same width A/B: 3 mm

Technical description

Collar thickness b ±0.1	1.9 mm
Bore Ø H6 d ₁	16 mm
Tooth height Zh	8 mm
Capability of combining 2 cutters of the same width A/B	3 mm
Capability of combining 2 cutters of different width A	3 mm
Capability of combining 2 cutters of different width, results in overall width E	6.6 - 6.8 mm
Feed f _z in steel < 900 N/mm ²	0.04 mm
Capability of combining 2 cutters of different width B	4 mm
No. of teeth Z	14
Capability of combining 2 cutters of the same width, results in overall width E	5.7 - 5.8 mm
Cutting width	3 mm
Cutting edge $Ø D_c$	50 mm
Collar \emptyset d ₂ ±1	34 mm
Shank type	with bore
Coating	TiAIN
Tool material	Solid carbide
Standard	DIN 885 A
Туре	Ν
Tolerance nominal Ø	± 0.1
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Machining strategy	HPC
Through-coolant	no
Colour ring	without
Type of product	Side milling cutter