Garant

Solid carbide side milling cutter HPC, TiAlN, Ø×width ± 0.1×k11: 50X4 mm



Order data

Order number	185010 50X4
GTIN	4045197366979
Item class	11V

Description

Version:

Precision solid carbide side milling cutters in the HPC machining range.

Use as a set: Cutters with the same Ø and same number of teeth can be combined as a set and adjusted to the required width. Since the cutters have no raised bore collar, the staggered teeth mesh with each other.

2-piece sets are particularly economical. By reversing the side milling cutters, both side edges of each cutter can be used.

Note:

- Do not clamp the cutters in a set without a sufficiently thick arbor spacer ring, otherwise the cutters will be damaged.
- See Group 30 for suitable arbor spacer rings.

• Slots milled from solid: f_z for $a_e = 0.1 \times D$.

Bore \emptyset H6 d₁: 16 mm No. of teeth Z: 14 Collar thickness b ±0.1: 2.8 mm Collar \emptyset d₂ ±1: 34 mm Tooth height Zh: 8 mm Capability of combining 2 cutters of the same width A/B: 4 mm

Technical description

No. of teeth Z	14
Capability of combining 2 cutters of the same width, results in overall width E	7.7 - 7.8 mm
Capability of combining 2 cutters of different width B	5 mm
Collar $Ø d_2 \pm 1$	34 mm
Collar thickness b ±0.1	2.8 mm
Bore Ø H6 d ₁	16 mm
Cutting width	4 mm
Capability of combining 2 cutters of different width A	4 mm
Capability of combining 2 cutters of the same width A/B	4 mm
Capability of combining 2 cutters of different width, results in overall width E	8.1 - 8.8 mm
Tooth height Zh	8 mm
Cutting edge Ø D _c	50 mm
Feed f _z in steel < 900 N/mm ²	0.04 mm
Shank type	with bore
Coating	TiAIN
Tool material	Solid carbide
Standard	DIN 885 A
Туре	Ν
Tolerance nominal Ø	± 0.1
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Machining strategy	HPC
Through-coolant	no
Colour ring	without
Type of product	Side milling cutter