Garant

GARANT Master Alu FEED solid carbide drill, plain shank DIN 6535 HA, uncoated, Ø DC h7: 8,4mm



Order data

Order number	122590 8,4
GTIN	4062406711764
Item class	11E

Description

Version:

3-cutter tool, specially developed for use at **very high feed rates** in aluminium. Outstandingly suitable for machines with **high power consumption** and stable machining conditions.

- Specially developed cutter geometry, designed for very high feed rates, reduced cutting pressure and controlled chip breaking.
- $\cdot\,$ Precision flute profile for reliable evacuation of chips.
- \cdot Achieve outstanding feed rates and tool life thanks to the third cutting edge.

The sector-leading technology of the drill point for the tool guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$. HB and HE shanks are available at the same price as HA. For **HB:** use order **No. 122591**. For **HE:** use order **No. 122590 + 129100HE**.

Technical description

Flute length L_c	61 mm
Nominal Ø D _c	8.4 mm
Tolerance nominal Ø	h7
Shank Ø D _s	10 mm
Standard	DIN 6537

Data sheet

recommended maximum drilling depth L_2	48.4 mm	
Feed f in aluminium short-chipping	0.92 mm/rev.	
Number of cutting edges Z	3	
Overall length L	103 mm	
Series	Master Alu	
Coating	uncoated	
Tool material	solid carbide	
Version	6×D	
Туре	W	
Point angle	130 degrees	
Shank	DIN 6535 HA to h6	
Through-coolant	yes, with 25 bar	
Machining strategy	HPC	
Semi-Standard	yes	
Colour ring	yellow	
Type of product	Jobber drill	

User data

	Suitability	V _c	ISO code
Alu plastics	suitable	300 m/min	Ν
Aluminium (short chipping)	suitable	250 m/min	Ν
Alu > 10% Si	suitable	200 m/min	Ν
CuZn	suitable	200 m/min	Ν
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		

Services

Shank grinding Type HE	129100 HE	
	-	

© Hoffmann GmbH Qualitätswerkzeuge