

UNO pre-setting device, Type: UPCAM



Order data

Order number	355020 UPCAM
GTIN	4034221174659
Item class	34H

Description

Version:

- · Large multi-touchscreen with intuitive and simple Microvision interface.
- · Calibration device on the SK50 tool mounting.
- · Wide variety of storage options, e.g. for tool arbors, adapters and controls such as a mouse, keyboard and printer.
- · Quick adjustment of both axes using Release-by-Touch (X/Z), separately or at the same time.
- · Fine adjustment of both axes (X / Z) using rotary wheel.
- · Spindle with 4×90° and 3×120° indexing and pneumatic spindle brake for turning tools.
- · Camera with 32x magnification.

The device operates in conjunction with the optional Hoffmann Group Connected software solutions for use in production environments.

Advantage:

Hoffmann Group Connected

With this article you are gaining a building block for your digitally networked production. Increased productivity can be achieved together with the respective software module.

Application:

For measuring and pre-setting tools at the machine in production or when planning work. **Supplied with:**



Keyboard, mouse, thermal label printer with labels, cutting edge cleaner, external camera for photo management, subframe cupboard (one swing door, three drawers), measurement software in all major foreign languages, **commissioning and training included (1 day).**

Optional extras:

The Haimer pre-setting devices are compatible with the GARANT reducers No. 354771; 354773; 354775; 354777 and 354779. Haimer reducers are available on request.

Note:

The connection for transferring data from the pre-setting device to the machine tool using the post-processor is included. A compatibility check against the standard HAIMER post-processors is required in advance. If your machine is not included in this standard package, additional costs may be incurred.

Other UNO models (autofocus and automatic drive) and VIO series available on request.

Technical description

Overall width	2264 mm
Width base	1294 mm
Base toolholder	SK50 ultra precision spindle
Weight	300 kg
Measuring range Z	400 mm
Depth	590 mm
Spindle load	30 kg
Measuring range X	400 mm
Quick adjustment	pneumatic
Second camera in the lens carrier	yes
Overall height	1735 mm
Snap gauge X	100 mm
Series	Hoffmann Group Connected
Interface	Hoffmann Group Connected
Display size	22 in
Type of product	Setting master