


Garant
**GARANT Diabolo solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / DS:
0,3mm**

Order data

| | |
|--------------|---------------|
| Order number | 207342 0,3 |
| GTIN | 4045197599544 |
| Item class | 11X |

Description
Version:
GARANT Diabolo:

Special geometry, coating and carbide for hard machining.

Tolerance: Radius contour = ± 0.005 mm.

Technical description

| | |
|---|---------------|
| No. of teeth Z | 2 |
| Cutting edge $\varnothing D_c$ | 0.3 mm |
| Feed f_z for side milling in steel < 65 HRC | 0.005 mm |
| Feed f_z for copy milling in steel < 65 HRC | 0.005 mm |
| Shank $\varnothing D_s$ | 3 mm |
| Overall length L | 38 mm |
| Flute length L_c | 1 mm |
| Helix angle | 30 degrees |
| Radius R | 0.15 mm |
| Series | Diabolo |
| Coating | TiAlN |
| Tool material | Solid carbide |

| | |
|---|----------------------------------|
| Standard | Manufacturer's standard |
| Type | H |
| Tolerance nominal \varnothing | f8 |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a_e for milling operation | 0.2×D for side milling |
| Cutting width a_e for milling operation | 0.05×D for copy milling |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | no |
| Machining strategy | HPC |
| Colour ring | red |
| Type of product | Ball-nosed slot drill |

User data

| | Suitability | V_c | ISO code |
|--------------------------------|---|-----------|----------|
| Steel < 1400 N/mm ² | suitable | 200 m/min | P |
| Steel < 50 HRC | suitable | 190 m/min | H |
| Steel < 55 HRC | suitable | 170 m/min | H |
| Steel < 60 HRC | suitable | 150 m/min | H |
| Steel < 65 HRC | suitable | 110 m/min | H |
| wet maximum | suitable only under restricted conditions | | |
| wet minimum | suitable only under restricted conditions | | |
| dry | suitable | | |
| Air | suitable | | |