

HAIMER MILL end mill, AlTiN, Ø f9 DC: 20mm



Order data

Order number	220291 20
GTIN	2050002068292
Item class	26X

Description

Version:

For **general-purpose use** in steel materials and high-alloy steels, especially stainless steel. With **cylindrical core** for optimised tool stiffness when milling slots. Reliable processes guaranteed when ramping and during circular interpolation milling thanks to **special end face geometry.**

Note:

For **HB** use order **No. 220291**.

Tool holders with the SAFE-LOCK pull-out protection can be found under clamping technology.

Technical description

Tolerance nominal ∅	f8	
Shank	DIN 6535 HB to h6	
Shank Ø D _s	20 mm	
Feed f_z for slot milling in steel < 900 N/mm ²	0.11 mm	
Overhang length L ₁ incl. recess	52 mm	
Flute length L _c	38 mm	
Feed f_z for side milling in steel < 900 N/mm ²	0.13 mm	
Helix angle	32 degrees	
Direction of infeed	horizontal, oblique and vertical	
Corner chamfer angle	90 degrees	
No. of teeth Z	4	

Recess Ø D ₁	19 mm	
Cutting edge \varnothing D_c	20 mm	
Overall length L	105 mm	
Coating	AlTiN	
Tool material	Solid carbide	
Standard	DIN 6527	
Туре	N	
Helix angle characteristic	unequal spacing	
Spacing of the cutters	unequal spacing	
Cutting width a _e for milling operation	0.05×D for side milling	
Cutting width a _e for milling operation	0.5×D for side milling	
Through-coolant	no	
Machining strategy	HPC	
Colour ring	without	
Type of product	End / face mill	

User data

	Suitability	V _c	ISO code
Alu plastics	suitable only under restricted conditions		
Aluminium (short chipping)	suitable only under restricted conditions		
Alu > 10% Si	suitable only under restricted conditions		
Steel < 500 N/mm ²	suitable		
Steel < 750 N/mm ²	suitable		
Steel < 900 N/mm ²	suitable		
Steel < 1100 N/mm ²	suitable		
INOX < 900 N/mm ²	suitable		
INOX > 900 N/mm ²	suitable		

Ti > 850 N/mm ²	suitable only under restricted conditions	
GG(G)	suitable only under restricted conditions	
Uni	suitable	
Oil	suitable	
wet maximum	suitable	
wet minimum	suitable	
dry	suitable	
Air	suitable	