#### HAME

## HAIMER MILL solid carbide torus cutter, AlTiN, Ø f9 DC / R1: 20/2,0mm



## Order data

	220297 20/2,0
GTIN	2050002068636
Item class	26X

## Description

#### Version:

For **general-purpose use** in steel materials and high-alloy steels, especially stainless steel. With **cylindrical core** for optimum tool stiffness when milling slots. Reliable processes guaranteed when ramping and during circular interpolation milling thanks to **special end face geometry. Note:** 

#### For **HB** use order **No. 220297**.

Tool arbor with the SAFE-LOCK pull-out protection can be found under clamping technology.

### **Technical description**

Overall length L	105 mm	
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.11 mm	
Flute length L <sub>c</sub>	38 mm	
Overhang length L <sub>1</sub> incl. recess	52 mm	
Helix angle	32 degrees	
Cutting edge $Ø D_c$	20 mm	
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.13 mm	
Corner radius R <sub>1</sub>	2 mm	
Recess Ø D <sub>1</sub>	19 mm	
Shank $\emptyset$ D <sub>s</sub>	20 mm	
Shank	DIN 6535 HB to h6	

© Hoffmann GmbH Qualitätswerkzeuge

No. of teeth Z	4	
Coating	AlTiN	
Tool material	Solid carbide	
Standard	DIN 6527	
Туре	Ν	
Tolerance nominal Ø	f9	
Helix angle characteristic	unequal spacing	
Spacing of the cutters	unequal spacing	
Direction of infeed	horizontal, oblique and vertical	
Cutting width $a_e$ for milling operation	0.05×D for side milling	
Cutting width $a_e$ for milling operation	0.5×D for side milling	
Through-coolant	no	
Machining strategy	HPC	
Type of product	Torus cutter	

## User data

	Suitability	V <sub>c</sub>	ISO code
Alu plastics	suitable only under restricted conditions		
Aluminium (short chipping)	suitable only under restricted conditions		
Alu > 10% Si	suitable only under restricted conditions		
Steel < 500 N/mm <sup>2</sup>	suitable		
Steel < 750 N/mm <sup>2</sup>	suitable		
Steel < 900 N/mm <sup>2</sup>	suitable		
Steel < 1100 N/mm <sup>2</sup>	suitable		
INOX < 900 N/mm <sup>2</sup>	suitable		
INOX > 900 N/mm <sup>2</sup>	suitable		

# Data sheet

Ti > 850 N/mm <sup>2</sup>	suitable only under restricted conditions	
GG(G)	suitable only under restricted conditions	
Uni	suitable	
Oil	suitable	
wet maximum	suitable	
wet minimum	suitable	
dry	suitable	
Air	suitable	