

Garant
GARANT Master Tap Alu machine tap for wire thread inserts, DLC, EG-M: EG-M2

Order data

Order number	133555 EG-M2
GTIN	4067263829782
Item class	111

Description
Version:

High-performance tap, specially developed for **aluminium and non-ferrous alloys**. **Extra-long flutes** and neck length for usable **thread depths up to 4xD**.

- **HSS-E-PM tool material for high cutting edge stability.**
- **Ultra-smooth DLC coating for wear resistance and avoidance of edge build-up.**
- **Extra-long flute geometry.**

Application:

For production of EG mounting thread according to metric ISO thread **DIN 8140** for **STI wire thread inserts** (Screw Thread Insert).

Note:

Please be sure to observe the correct **tapping hole Ø (see table)**!

Technical description

Tapping hole Ø	2.15 mm
Tool material	HSS E PM
Thread pitch	0.4 mm
Thread Ø	2 mm
Number of cutting edges Z	2
Number of clamping slots	2
Tolerance class	6HX mod.
Standard	Works standard

Shank $\varnothing D_s$	2.8 mm
Shank square \square	2.1 mm
Overall length L	55 mm
Thread depth	8 mm
Coating	DLC
Thread type	EG-M
Flank angle	60 degrees
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 4xD for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	yellow
Series	Master Tap
Type of product	Taps

User data

	Suitability	V_c	ISO code
Aluminium	suitable	35 m/min	N
Aluminium (short chipping)	suitable	32 m/min	N
Alu > 10% Si	suitable	20 m/min	N
PMMA acrylic	suitable only under restricted conditions	20 m/min	N
PA 66	suitable only under restricted conditions	18 m/min	N
PEEK	suitable	18 m/min	N
Cu	suitable	18 m/min	N
CuZn	suitable	25 m/min	N

Oil	suitable
wet maximum	suitable
wet minimum	suitable