



Lifting magnet LM, maximum loading capacity (level): 125kg



Order data

Order number	085992 125
GTIN	2050001737571
Item class	08P

Description

Version:

Compact, robust design with neodymium permanent magnets. Optimum performance even with large air gaps, no stray fields. Certified break-away force (see **test certificate**). Sturdy and compact lifting magnet with low overall weight and with safety-locking mechanism. Ergonomic clamping lever permits easy action on/off switching.

Application:

For safe handling and transporting of flat and round materials (No. 085990; 085992; 085995) or of thin flat materials (No. 085985).

For steel or cast iron parts, plates, rods or pipes. For use in warehouses, foundries / steelworks, storage of steel, tool-making, and production areas.

Test certificate: Manufacturer's test certificate

maximum \varnothing round: 250 mm

maximum length flat: 1500 mm

minimum material wall thickness, flat: 20 mm

minimum material wall thickness, round: 13 mm

Dimension A: 110 mm

Dimension B: 150 mm

Technical description

maximum lifting capacity round	50 kg
minimum material wall thickness, round	13 mm

Dimension B	150 mm
maximum Ø round	250 mm
Dimension E	54 mm
minimum material wall thickness, flat	20 mm
maximum length flat	1500 mm
Dimension G	26 mm
maximum lifting capacity flat	125 kg
Dimension A	110 mm
Dimension C	76 mm
Weight	4.5 kg
Dimension D	62 mm
Dimension F	150 mm
Test certificate	Manufacturer's test certificate
Type of product	Lifting magnet