

Garant

Solid carbide ball nose slot drill, Diamond, Ø e8 DC: 5 mm



Order data

Order number	209785 5
GTIN	4045197476135
Item class	11Y

Description

Version:

With the latest generation of **crystalline diamond coating sp³** for process reliability in machining **fibre-reinforced composites, CRP, GRP and graphite**. Taper transition **with 1°30' (angle α)**.

Tolerance: Radius contour = **±0.01 mm**.

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Flute length L_c: 6 mm

Overhang length L₁ incl. recess: 20 mm

Recess Ø D₁: 4.8 mm

Overall length L: 80 mm

Shank Ø D_s: 6 mm

Technical description

Cutting edge Ø D _c	5 mm
L ₂	40 mm
Recess Ø D ₁	4.8 mm
Ø D ₂	5.9 mm
Feed f _z for copy milling in graphite	0.062 mm
No. of teeth Z	2
Overhang length L ₁ incl. recess	20 mm
Shank Ø D _s	6 mm

Overall length L	80 mm
Flute length L _c	6 mm
Helix angle	30 degrees
Radius R	2.5 mm
Coating	Diamond
Tool material	Solid carbide
Standard	Manufacturer's standard
Tolerance nominal Ø	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width a _e for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA with h6
Through-coolant	no
Colour ring	black
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------