

Platform scales, type DS high resolution, maximum weighing range: 65kg



Order data

Order number	479611 65
GTIN	4045761356993
Item class	47D

Description

Version:

- Robust platform scales can be used as parcel, industrial, and counting scales.
- Display unit with numeral height 21 mm can be remote from platform; can be stood or mounted using flexible cable.
- · Robust platform with a protective hood over the display unit.
- · Simple, self-explanatory user guidance with (yes/no) dialogue in the display.
- · Selectable mains or battery operation (battery available on request).
- Units of weight (e. g. screw weight) can be freely programmed.
- · With automatic reference optimisation for exact counting.
- · Adjustment programme CAL: For accuracy adjustment (required calibration weight available on request).
- Quantity counting: Reference quantities selectable 1, 5, 10, 20 pieces.
- · Display selectable between pieces and weight.
- · Numeric tare preference for well-known container weight. Useful for filling quantities.
- · Percentage determination: Display of deviation from the reference weight in % instead of in grammes.
- KERN Universal Port (KUP): allows the connection of external KUP interface adapters (not included) such as RS-232, USB for exchanging data and control commands, without installation effort.

Supplied with:

Mains adapter 230 V / 50 Hz and protective hood.

Optional extras:



Internal and external rechargeable battery, calibration weight, wall attachments, printer, stand and interface adapter such as RS-232, USB on request.

Technical description

Settling time	3 s
Net weight	19 kg
Power supply	Mains operated
Manufacturer's designation	DS
Dimensions of weighing plate	500×400 mm
Scale divisions	0.5 g
Reproducibility	0.5 g
Minimum unit weight	5 g
Calibration	Price on request
maximum weighing range	0 - 65 kg
Number height display unit	18 mm
Type of product	Platform balance

Services

CalibrationScales maximum weighing range 100 kg	027700 100
DAkkS calibrationScales maximum weighing range 180	027710 180