Garant

Burr GARANT Master Alu – very rough (non-ferrous / aluminum), Carbide DLC, Type: F1225



Order data

Order number	547600 F1225		
GTIN	4067263736554		
Item class	51D		

Description

Version:

GARANT burrs are manufactured from the highest quality carbide with high wear resistance and maximum cutting edge strength, using only the latest CNC machines. Steel shanks are used when the head diameter is larger than the shank diameter, otherwise they are made from solid carbide.

The newly developed innovative tooth geometry permits very high metal removal rates combined with smooth cutting and good guidance accuracy. No chip adhesion and excellent surface results. Shank \emptyset 6mm. Suitable for use in roughing and finishing applications. With high-performance coating for longer tool life, less heat input and reduced chip adhesion.

- · High rate of material removal.
- · Smooth running.
- · High-performance coating for low thermal stress, longer tool life, and improved chip evacuation.
- · State-of-the-art substrate optimised for aluminium materials.
- · Maximum tool life.

Application:



Optimised for machining hard and soft aluminum alloys, plastics, bronze and non-ferrous metals. Suitable for both manual and industrial robots. For deburring, edge breaking, cleaning, weld and surface preparation.

Note:

Materials with poor heat conductivity; reduce speed to avoid overheating of the burr and smearing.

Technical description

Toothing grit designation	very coarse		
Head length	25 mm		
Shank Ø	6 mm		
Shape	F1225		
Overall length	65 mm		
Head ∅	12 mm		
Shape description	round arch		
Series	GARANT Master Alu		
Tool material	Carbide DLC		
Type of product	Burr		

User data

	Suitability	V _c	ISO code
Alu Mg	suitable		
CuZn	suitable		
Plastic, GRP	suitable only under restricted conditions		