


### Solid carbide deburrer, spiral flutes 90°, TiSiN, Ø h6 DC: 12mm



### **Order data**

Order number	GG8156 12
GTIN	4067263091332
Item class	GGN

## **Description**

#### **Version:**

#### Same as No. 208156.

Deburrer for **universal application** on virtually all materials. The newly developed coating effectively prevents built-up edges, even in aluminium or stainless steel.

Tolerance: **Dimension S = \pm/- 0.2 mm.** 

Point angle = +/- 5 arc minutes.

Outstanding surface qualities thanks to the 35° helix angle.

#### **Application:**

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

# **Technical description**

Corner chamfer angle	45 degrees
Cutting edge Ø D <sub>c</sub>	12 mm
Overall length L	83 mm
Feed $f_z$ in steel < 900 N/mm <sup>2</sup>	0.08 mm
Chamfer mill	45 degrees

Shank	DIN 6535 HA to h6	
Contents	5	
No. of teeth Z	4	
Dimension S	8.5 mm	
Shank Ø D <sub>s</sub>	12 mm	
Coating	TiSiN	
Tool material	Solid carbide	
Standard	Works standard	
Туре	N	
Tolerance nominal Ø	h6	
Helix angle	35 degrees	
Direction of infeed	horizontal, oblique and vertical	
Countersink tip angle	90 degrees	
Through-coolant	no	
Shank tolerance	h6	
Colour ring	green	
Type of product	Deburrers	

## **User data**

	Suitability	<b>V</b> <sub>c</sub>	ISO code
Alu plastics	suitable only under restricted conditions	180 m/min	N
Aluminium (short chipping)	suitable	300 m/min	N
Alu > 10% Si	suitable	220 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	130 m/min	Р
Steel < 750 N/mm <sup>2</sup>	suitable	115 m/min	Р
Steel < 900 N/mm <sup>2</sup>	suitable	110 m/min	Р
Steel < 1100 N/mm²	suitable	80 m/min	Р



Steel < 1400 N/mm <sup>2</sup>	suitable only under restricted conditions	65 m/min	Р
Steel < 55 HRC	suitable only under restricted conditions	35 m/min	н
INOX < 900 N/mm <sup>2</sup>	suitable	90 m/min	M
INOX > 900 N/mm <sup>2</sup>	suitable	70 m/min	M
Ti > 850 N/mm <sup>2</sup>	suitable	50 m/min	S
GG(G)	suitable	100 m/min	K
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable only under restricted conditions		
dry	suitable only under restricted conditions		
Air	suitable only under restricted conditions		

## **Accessories**

Solid carbide deburrer, spiral flutes90° Ø h6 DC 12 mm	208156 12
--	-----------