Åo Garant*

Softcut[®] 90° indexable milling cutter MTC, with bore, Ø D / Zeff: 63/5_ mm

Order data	
Order number	215161 63/5_
GTIN	4045197455086
Item class	210

Description

Version:

High precision square shoulder milling cutter with irregular pitch for very smooth cutting, very high precision and cutting power. High performance indexable square shoulder milling cutter with special geometry for reduced cutting forces for MTC applications under unstable conditions or for spindles with low drive power.

Description:

The insert pocket must be modified when using indexable inserts with a radius greater than 3.1 mm.

Application:

For corner milling to large depths, also slotting. General use in all steels including stainless steels. Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres **(MTM).**

Note:

Use GARANT torque screwdriver TQ No. **211750 size 3.8** with bit No. **674252 size 15IP**. The insert pocket must be modified when using indexable inserts with a radius greater than 3.1 mm.

Setting angle κ: 90 degrees

Milling application: Corner milling

Milling application: Ramping

Milling application: Circular milling

Spacing of the milling cutter's cutting edges: unequal spacing

Through-coolant: true

Technical description

Milling application	Corner milling
Milling application	Ramping
Milling application	Circular milling

Shank type	with bore
Setting angle ĸ	90 degrees
Through-coolant	yes
Machining strategy	MTC
Spacing of the cutters	unequal spacing
Norm	
Туре	
Coating	
Tool material	
Tool exchange	PowerCard
Type of product	