GARANT Master Alu solid carbide finishing cutter HPC, uncoated, Ø h6 DC: 10mm



Order data

Order number	203213 10
GTIN	4067263100324
Item class	11X

Description

Version:

For fine finishing operations. Cutter geometry optimised for low infeeds and excellent surfaces. Unequal spacing gives high intrinsic stability and smooth cutting action.

Application:

For profile milling as a finishing operation.

Note:

Optimal production results in conjunction with the GARANT HiRunER precision ER collet chuck, GARANT Master Chuck hydraulic chuck and heavy-duty chuck.

Technical description

Tolerance nominal Ø	h6	
Cutting edge Ø D _c	10 mm	
rection of infeed horizontal		
Overhang length L ₁ incl. recess	36 mm	
Shank Ø D _s	10 mm	
Helix angle	40 degrees	
No. of teeth Z	7	
Feed f_z for side milling in short-chipping aluminium	0.035 mm	
Overall length L	80 mm	
Corner chamfer angle	90 degrees	



Shank	DIN 6535 HA to h6		
Balance quality with shank	G 2.5 with HA		
Flute length L _c	32 mm		
Recess Ø D ₁	9.5 mm		
Series	Master Alu		
Coating	uncoated		
Tool material	Solid carbide		
Standard	Works standard		
Туре	W		
Helix angle characteristic	unequal spacing		
Spacing of the cutters	unequal spacing		
Milling application	Mono milling tools high-precision 90°		
Cutting width a _e for milling operation	0.025×D for side milling		
Through-coolant	no		
Machining strategy	HPC		
Colour ring	yellow		
Type of product	End / face mill		

User data

	Suitability	\mathbf{V}_{c}	ISO code
Alu plastics	suitable	380 m/min	N
Aluminium (short chipping)	suitable	360 m/min	N
Alu > 10% Si	suitable only under restricted conditions	320 m/min	N
PMMA acrylic	suitable	260 m/min	N
PE-HD	suitable	220 m/min	N
PA 66	suitable	250 m/min	N
PEEK	suitable	220 m/min	N

PF 31	suitable	200 m/min	N
Cu	suitable only under restricted conditions	160 m/min	N
CuZn	suitable	220 m/min	N
wet maximum	suitable		
wet minimum	suitable		
Air Services	suitable		

Shank grinding Type HB

129100 HB