

ISCAR SUMOCHAM drilling head HCP-IQ k7, IC908, Ø DC: 14mm



Order data

Order number	231745 14
GTIN	7291075333398
Item class	23J

Description

Version:

Vee ground drilling head for precise positioning and stable seating. Angled, **radial stop surfaces** for a significant increase in clamping force due to the cutting forces acting during machining. For productive drilling with **high feed rates.**

HCP-IO

Main area of application ISO P and ISO K. Best possible centring capability, machining of curved surfaces. Not for use in ductile materials.

Note:

Cutting data applies for the base body 5×D. Drill pilot holes exclusively with drilling head of the same type – in particular for drilling heads FCP and QCP-2M. Please observe the application instructions for the base body. Cutting tolerance of the inserts: **k7** (positive toleranced cutting edge diameter).

Designation convention: [type] [\varnothing D_c]-[addition] [cutting material]

Examples:

No. 231740 6.5 ICP 065 IC908

No. 231742 18.5 ICP 185-2M IC908

No. 231745 18.5 HCP 185-IQ IC908 The minimum order quantity corresponds to one pack unit quantity (VPE) or a multiple thereof.

Technical description

Feed f in steel < 900 N/mm ²	0.26 mm/rev.		
for base body size	14		
Ø D	14 mm		
Coating	TiAIN		
Series	SUMOCHAM		
Number of changes/inserts	2		
Iscar item designation	HCP 140-IQ IC908		
Geometry	HCP-IQ		
Point angle	137 degrees		
Manufacturer's designation	HCP 140-IQ IC908		
Grade	IC908		
Tool material	Carbide		
Type of product	Drilling head for boring		

User data

	Suitability	V _c	ISO code
Steel < 500 N/mm ²	suitable	100 m/min	Р
Steel < 750 N/mm ²	suitable	90 m/min	Р
Steel < 900 N/mm ²	suitable	100 m/min	Р
Steel < 1100 N/mm ²	suitable	70 m/min	Р
Steel < 1400 N/mm ²	suitable	55 m/min	Р
TOOLOX 33	suitable only under restricted conditions	70 m/min	Н
TOOLOX 44	suitable	60 m/min	Н
GG(G)	suitable only under restricted conditions	120 m/min	К
CuZn	suitable only under restricted conditions	155 m/min	N

Oil	suitable only under restricted conditions	
wet maximum	suitable	