

HELI3MILL shoulder mill, with bore, \varnothing DC / number of effective cutting edges Z: 50/5mm



Order data

Order number	226490 50/5
GTIN	7291075313284
Item class	19D

Description

Version:

Reliable shoulder milling system for a wide range of applications. Versions in two system sizes with cutting edge lengths in 10 and 15 mm. Optimally supported Trigon indexable inserts in the seat ensure true 90° shoulders. Ideally suited for circular interpolation milling operations and ramping.

Spare part:

Pack of insert screws No. 229696 1 (IP20; 9.0 Nm).

Technical description

Circular interpolation milling a _p	3.9 mm
\emptyset D ₃	45.6 mm
Cutting edge Ø D _c	50 mm
Ramping angle α_{max}	1.6 degrees
Number of cutting edges Z	5



Circular interpolation milling \emptyset D_{max}	99 mm
Ramping length L for α_{max}	468.99 mm
Circular interpolation milling \emptyset D_{min}	95 mm
Series	HELI3MILL
Overall length L _{tot}	40 mm
Mounting bore \varnothing	22 mm
Manufacturer's designation	HM390 FTD D050-5-22-15
Shank type	with bore
Setting angle κ	90 degrees
Milling application	Plunging
Milling application	Plunging
Milling application	Ramping
Through-coolant	yes
Machining strategy	HPC
Type of product	End / face mill

Accessories

Set of insert screws10 pieces Type 1	229696 1
--------------------------------------	----------