## KOMET KOMET KUB Trigon<sup>®</sup> indexable drill ABS 50, 3×D, Ø DC: 23mm



## Order data

Order number	236635 23
GTIN	4047109099593
Item class	24P

## Description

Version:

- · Special manufacturing procedure for extremely large flutes with very high rigidity.
- Specific positioning of the indexable inserts for bores free of withdrawal marks and with precise dimensional stability(± 0.1 mm as a rule).
- Internal coolant supply is directed to the cutting edges (sophisticated geometry, ideal for minimum lubrication).
- · 3 10 bar coolant pressure is sufficient.
- · For stationary and rotating applications.
- · Offset-axis drilling: dependent on Ø up to 1.5 mm.

#### **Application:**

With indexable inserts No. 236740 – 237080.

#### Supplied with:

Clamp screws (without indexable inserts).

#### Note:

- Note! A disc falls off when the drill exits. Risk of injury if the component is rotating! Please take safety precautions.
- On request left-hand cutting; 2×D, other Ø; special types torsional vibration damper for ABS giving low-vibration machining, with maximum tool life and minimum noise level.

### **Technical description**

Pack of insert screws	239652 6IP2 (1.0 Nm)
achievable maximum Ø offset	24 mm

Reach L <sub>1</sub>	69 mm
Number of cutting edges Z	1
ABS® shank Ø D <sub>s</sub>	50 mm
ISO code indexable insert	WOEX 040304 18
Series	KUB Trigron®
Nominal Ø D	23
for inch Ø	29/32 in
Maximum adjustment limit V <sub>max</sub>	0.5 mm
Overhang L <sub>A</sub>	104 mm
Drill depth for indexable insert drill up to	3×D
Shank	ABS
Use for drilling	Centre drilling
Use for drilling	limited cross-drilling
Use for drilling	oblique spot drilling
Use for drilling	limited cross-drilling
Use for drilling	Aperture
Use for drilling	oblique exit
Use for drilling	convex
Through-coolant	yes
Type of product	Indexable drill

# Accessories

Torx Plus <sup>®</sup> insert screw set10 pieces Drive 6IP2	239652 6IP2
PrecisionBit for Torx Plus <sup>®</sup> , 1/4 inch E 6.3 Torx Plus <sup>®</sup> profile 6IP	674252 6IP
Torque screwdriver, fixed setting set torque 1,0 N·m	211750 1,0