

Garant**Burr GARANT Master Alu – very rough (non-ferrous / aluminum), Carbide DLC,
Type: F1225****Order data**

Order number	543710 F1225
GTIN	4067263117940
Item class	51D

Description**Version:**

No chip adhesion and outstanding surface results. Shank \varnothing 6mm. Suitable for use in roughing and finishing applications. With high-performance coating for longer tool life, less heat input and reduced chip adhesion.

- **High rate of material removal.**
- **Smooth running.**
- **High-performance coating for low thermal stress, longer tool life, and improved chip evacuation.**
- **State-of-the-art substrate optimised for aluminium materials.**
- **Maximum tool life.**

GARANT burrs are manufactured from the highest quality carbide with high wear resistance and maximum cutting edge strength, using only the latest CNC machines. Steel shanks are used when the head diameter is larger than the shank diameter, otherwise they are made from solid carbide.

The innovative tooth geometry permits a high metal removal rate and at the same time extremely smooth running and very good guidance. Extra-sturdy shank with 8 mm.

Application:

For the most demanding burring operations.

Optimised for machining hard and soft aluminium alloys, plastics, bronze and non-ferrous metals.

Suitable for both manual use and industrial robots. For deburring, edge breaking, cleaning, weld and surface preparation.

Note:

Materials with poor thermal conductivity: Reduce speed in order to avoid overheating the burr and smearing.

Technical description

Head Ø	12 mm
Shape description	round arch
Shank Ø	8 mm
Overall length	65 mm
Head length	25 mm
Tool material	Carbide DLC
Type of product	Burr