

**TESA**

**Digital caliper SET TESA-CAL IP67, measurement range 150 mm, Number of digital calipers: 3**



## Order data

|              |               |
|--------------|---------------|
| Order number | 405522 3      |
| GTIN         | 4067263132776 |
| Item class   | 45A           |

## Description

### Version:

- **Perfect guidance of the slide on the rail for easy and even smooth running.**
- **Sturdy design for long life and long-term stability of results.**
- **High protection category against dust and liquids.**
- **Easy to read with large, sharp-contrast round scale.**
- **Long battery life avoids frequent changing of batteries.**

### Function:

IP67: Protected against intermittent immersion in water and protected against penetration by dust (dust-tight), also completely protected against touching.

### Application:

External, internal, step and depth measurements.

### Supplied with:

1 battery No. 081560 size CR2032. Set consisting of 3x No. 412760 size 150.

## Technical description

|  |                     |
|--|---------------------|
| Measurement deviation E MPE  | ±0.03 mm            |
| Measurement value and zero point preserved after reactivation from standby | yes                 |
| Depth gauge  | rectangular 3.7×1.3 |

|   |                                       |
|---|---------------------------------------|
| Auto switch-off   | yes                                   |
| Power supply  | Battery-powered                       |
| Jaw length  | 40 mm                                 |
| Reversible reading                                      | mm / inch                             |
| Number of batteries contained                           | 1                                     |
| Working time  | 12000 hours                           |
| Depth gauge available                                   | yes                                   |
| Standard  | ISO 13385                             |
| Measured value saving                                   | Once-off setting of the zero position |
| Calibration   | A1                                    |
| Measuring range   | 0 - 150 mm                            |
| Scale divisions   | 0.01 mm                               |
| Article no of the battery / rechargeable battery fitted | 081560 CR2032                         |
| IP Index of Protection                                  | IP 67                                 |
| Digit height LCD display                                | 11 mm                                 |
| Scale divisions   | 0.0005 in                             |
| Automatic stand-by circuit.                             | yes                                   |
| Measurement technology                                  | digital                               |
| Material  | Stainless steel, INOX                 |
| all parts   | hardened                              |
| Packaging   | sturdy box                            |
| Type of product   | Universal calipers                    |

## Services

|   |              |
|---|--------------|
| DAkkS calibrationCalipers / depth gauges maximum measuring range 3X200 mm | 021010 3X200 |
| CalibrationCalipers / depth gauges maximum measuring range 3X200 mm       | 021000 3X200 |

## Accessories

Button cell / special battery Battery type CR2032

081560 CR2032