

Garant

Torque screwdriver with 1/4 inch bit holder, with scale, automatic triggering, maximum torque: 120cNm



Order data

Order number	659100 120
GTIN	4067263117186
Item class	61E

Description

Version:

- **Ergonomically shaped power grip with easy-grip Haptoprene surface ensures high transmission of force.**
- **Clear and easy to read thanks to large numeric display.**
- **Short 36° trigger distance with clearly audible and perceptible signal.**
- **Trigger mechanism with 10 detent elements made of high-alloy tool steel with high wear resistance for a long service life.**
- **The overload clutch ("Slipper") ensures the set value is not exceeded.**
- **Easy to use and easy to identify the locked and unlocked state by the orange signal ring on the rotary knob.**
- **Bit holder (1/4 inch – D 6.3 / F 6.3) with quick release fastener. Fast bit changes with one hand.**

Function:

On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use. In the anti-clockwise direction of rotation: without torque function to loosen screw connections.

Standard:

Tested to **DIN EN ISO 6789**.

Accuracy:

±6 %.

Technical description

Resolution	1 cNm
------------	-------

Data sheet

Standard	DIN EN ISO 6789
Overall length L	204 mm
Release signalling	acoustic
Release signalling	haptic
maximum torque	120 cNm
Calibration	O1
Bit socket	D 6.3
Bit socket	F 6.3
Measurement technology	mechanical
Weight	310 g
Adjustable trigger value	adjustable
Setting the trigger value	with adjustment scale
Test certificate	Manufacturer's test certificate
Measurement process	Torque
Direction of tightening	Right-hand tightening
Torque measuring accuracy	±6 %
Connection format	Bit holder 1/4 inch
Reversible reading	cNm
Torque range	20 - 120 cNm
Data can be recorded	no
Feedback	acoustic signal
Feedback	triggering
Trigger principle	mechanical slip clutch
Display	analogue
Torque fixed setting	yes
Type of product	Torque screwdriver

Suitable products

<https://www.hoffmann-group.com/GB/en/hom/p/659100-120>

