# Garant

## Value pack abrasive flap disc long life ZA conical



#### **Order data**

| Order number | GG5265 40     |  |  |
|--------------|---------------|--|--|
| GTIN         | 4067263136781 |  |  |
| Item class   | GGN           |  |  |

## Description

#### **Version:**

- · Premium zirconium oxide (ZA) for maximum abrasive performance.
- Sturdy polyester cotton mixed fabric for ideal wear characteristics and stability, even when used on edges.
- · Sturdy glass fibre pad for optimum contact pressure.
- · Suitable for both steel and stainless steel.
- · Best results on low-power and high-power angle grinders.

long life - very closely spaced flap strips, for maximum tool life.

Corresponds to 565265.

### **Application:**

General purpose abrasive disc operations, surface abrasion, material removal and edge smoothing.

### **Technical description**

| Contents          | 100    |  |  |
|-------------------|--------|--|--|
| Shape description | dished |  |  |
| Grit              | 40     |  |  |

## Data sheet

| Bore Ø                                  | 22.23 mm                |  |  |
|---|-------------------------|--|--|
| Disc Ø                                  | 125 mm                  |  |  |
| Grinding media                          | Zirconium abrasive (ZA) |  |  |
| Grinding medium code                    | ZA                      |  |  |
| Iron, sulphur and chlorine constituents | < 0,1 %                 |  |  |
| Product name attribute                  | Ø 125 mm                |  |  |
| optimised for material                  | INOX                    |  |  |
| optimised for material                  | Steel                   |  |  |
| maximum circumferential speed           | 80 m/s                  |  |  |
| Type of product                         | Abrasive flap disc      |  |  |

## **User data**

|                                | Suitability                               | <b>V</b> <sub>c</sub> | ISO code |
|--------------------------------|---|-----------------------|----------|
| Steel < 900 N/mm <sup>2</sup>  | suitable                                  |                       |          |
| Steel < 1400 N/mm <sup>2</sup> | suitable                                  |                       |          |
| Steel < 55 HRC                 | suitable                                  |                       |          |
| Steel < 60 HRC                 | suitable                                  |                       |          |
| Steel < 67 HRC                 | suitable                                  |                       |          |
| INOX                           | suitable                                  |                       |          |
| Ti                             | suitable only under restricted conditions |                       |          |
| GG(G)                          | suitable                                  |                       |          |
| Uni                            | suitable                                  |                       |          |
| dry                            | suitable                                  |                       |          |

## **Suitable products**

https://www.hoffmann-group.com/GB/en/hom/p/GG5265-40