



BMT longitudinal toolholder, BMT: 60



Order data

Order number	319885 60
GTIN	4069515004237
Item class	32U

Description

Version:

High-precision arbors adapted to the specific machine, for flexible use on main and counter-spindle machines. Contact face and functional face ground. Perfectly matched for the respective lathe.

Suitable for conventional toolholders.

Advantage:

- **Design optimised for weight and geometry.**
- **Process reliability thanks to high-quality materials, long working life.**
- **Burnished for better corrosion protection.**
- **With secured ball spray nozzles up to 80 bar.**

Application:

Internal and external machining in CNC lathes with BMT tool turrets.

Mainly for external machining.

Suitable for:

CNC lathes with BMT tool turret.

- **DMG MORI: NLX 4000, NLX 1500, NLX 2000, NLX 2500, NLX 3000, NT 4200, NT 4250, NT 4300, NT 5400, NTX 2000 Generation 2, NTX 2500 Generation 2, NTX 3000 Generation 2**
- **TAKISAWA: TS-3000 T12 (3 T-nuts), TS-4000 T12 (3 T-nuts), TS-5000 T12 (3 T-nuts)**

Note:

Other BMT holders with different sizes and dimensions are available on request.

Please note that you must check the compatibility of the holder with your machine before purchasing. We cannot guarantee that it will fit correctly.

Technical description

h_2	108 mm
L_2	84 mm
x	70 mm
b_2	65 mm
L_1	94 mm
h_1	25 mm
Type of product	Steel toolholder