KOMET

KOMET KUB Trigon[®] indexable drill Combination shank, 3×D, Ø DC: 19,5mm



Order data

Order number	236630 19,5
GTIN	4047109100183
Item class	24P

Description

Version:

- Offset-axis drilling: dependent on Ø up to 1.5 mm.
- · Special manufacturing procedure for extremely large flutes with very high rigidity.
- Specific positioning of the indexable inserts for bores free of withdrawal marks and with precise dimensional stability (± 0.1 mm as a rule).
- Internal coolant supply is directed to the cutting edges (sophisticated geometry, ideal for minimum lubrication).
- · 3 10 bar coolant pressure is sufficient.
- · For stationary and rotating applications.

Application:

With indexable inserts No. 236740 – 237080.

Supplied with:

Clamp screws (without indexable inserts).

Note:

- Note! A disc falls off when the drill exits. Risk of injury if the component is rotating! Please take safety precautions.
- On request left-hand cutting; 2×D, other Ø; special types torsional vibration damper for ABS giving low-vibration machining, with maximum tool life and minimum noise level.

Technical description

ISO code indexable insert	WOEX 030204 10
Pack of insert screws	239652 6IP1 (0.6 Nm)
Number of cutting edges Z	1
achievable maximum Ø offset	20 mm

Reach L ₁	60 mm
Shank Ø D _s	25 mm
Shank length L _s	56 mm
Series	KUB Trigon®
Nominal Ø D	19.5
Maximum adjustment limit V _{max}	0.25 mm
Overhang L _A	84 mm
Drill depth for indexable insert drill up to	3×D
Shank	DIN 6535 HE, DIN 6595
Use for drilling	Centre drilling
Use for drilling	limited cross-drilling
Use for drilling	oblique spot drilling
Use for drilling	limited cross-drilling
Use for drilling	Aperture
Use for drilling	oblique exit
Use for drilling	convex
Through-coolant	yes
Type of product	Indexable drill

Accessories

PrecisionBit for Torx Plus [®] , 1/4 inch E 6.3 Torx Plus [®] profile 6IP	674252 6IP
Torque screwdriver, fixed setting set torque 0,6 N·m	211750 0,6
Torx Plus [®] insert screw set10 pieces Drive 6IP1	239652 6IP1