



## Short drill chuck Form A, SK 40, Clamping range: 1-13mm



### Order data

Order number	302540 1-13
GTIN	4045197307668
Item class	37D

### Description

**Version:**

For clockwise and anticlockwise rotation. Internal thread for manual clamping.

**Application:**

For clamping drills, countersinks, and reamers on milling machines.

**Supplied with:**

Hexagon screwdriver with T-handle.

### Technical description

Clamping range	1 - 13 mm
Overhang dimension A	80 mm
External Ø D	43 mm
Spare chuck key	SW6
Adapter	SK 40
Arbor standard	DIN 2080
Shape	A
maximum tightening torque $M_{d\max}$	≤ 14 Nm
Type of product	Short drill chuck

## Accessories

Pull stud, 18CrNiMo7sealed, form B suitable for steep tapers 40	308615 40
Pull studForm B suitable for steep tapers 40	308640 40
Hurco 45° pull stud with 4-mm bore and fitsealed suitable for steep tapers 40	308801 40
Pull studsealed suitable for steep tapers 40	308635 40
Pull stud 45°sealed suitable for steep tapers 40	308760 40
Pull stud 90°sealed suitable for steep tapers 40	308790 40
Pull studMori-Seiki, sealed, form A suitable for steep tapers 40	308625 40
Pull studForm A suitable for steep tapers 40	308600 40
Pull stud 90°sealed suitable for steep tapers 40	308795 40
Wrench for pull studsISO 7388 suitable for ISO taper size 40	308830 40
Pull studsealed, form B suitable for steep tapers 40	308620 40
Pull studMazak, form A suitable for steep tapers 40M	308670 40M
Special pull stud with internal thread suitable for steep tapers 40	308740 40
Pull stud, 18CrNiMo7Form A suitable for steep tapers 40	308605 40
Hexagon screwdriver, with T-handle Hexagon 6 mm	627481 6
Special pull stud with no internal threadsealed suitable for steep tapers 40	308700 40
Pull stud Hurco 90° with fitsealed suitable for steep tapers 40	308806 40
Pull stud 60°sealed suitable for steep tapers 40	308785 40
Wrench for pull studsDIN ISO 7388-1 (formerly DIN 69872) suitable for ISO taper size 40	308820 40
Pull studsealed, form B suitable for steep tapers 40	308650 40
Pull stud Hurco 45° with fitsealed suitable for steep tapers 40	308802 40
	308630 40

Pull stud Mori-Seiki, sealed, form A suitable for steep tapers  
40

Pull stud sealed suitable for steep tapers 40	308660 40
Pull stud sealed, form A suitable for steep tapers 40	308610 40
Pull stud 45° sealed suitable for steep tapers 40	308765 40