Garant

Softcut® chamfer mill with bore, for indexable inserts AO..



Order data

Order number	215403 15
GTIN	4069515038171
Item class	210

Description

Version:

Robust plug-in chamfer mill. Insert seat enclosed on several sides for stabilisation of the cutters and to take up the vertical and radial forces.

Application:

For wide chamfers in steel fabrications. Outstandingly suitable for roughing and semi-roughing applications.

Note:

Stepless surfaces are achieved with indexable inserts No. 215431-215487. Use GARANT torque screwdriver TQ No. **211750 size 1.5** with bit No. **674252 size 8IP**.

Technical description

Number of effective inserts $Z_{\mbox{\scriptsize eff}}$	3
Feed rate per tooth at h _{max}	0.4 mm
Number of indexable inserts	9
Angle γ	15 degrees
achievable chamfer height h	7.2 mm

Data sheet

Overall length L _{tot}	55 mm
Mounting bore Ø	22 mm
suitable indexable insert	AO.T1104
achievable chamfer length l	27.6 mm
achievable chamfer width b	26.6 mm
smallest Ø D	17 mm
largest Ø D₁	70 mm
Set of insert screws	219799 10 (8IP; 1.5 Nm)
Shank type	with bore
Spacing of the cutters	unequal spacing
Through-coolant	yes
Machining strategy	MTC
Tool exchange	PowerCard
Type of product	Chamfer mill

Suitable products

No Shop URL available for: 215403 15