

**GARANT GreenPlus liquid treatment agent, 5 l Steel, stainless steel, Grinding and polishing, Type: UNI****Order data**

Order number	501600 UNI
GTIN	4069515040235
Item class	58F

Description**Version:**

GARANT GreenPlus Compound UNI: for safer handling of your vibratory finishing machine. 5–7% of the liquid compound without hazard labels is added during the wet process in vibratory finishing machines. The probiotic ingredients and regular operation of the vibratory finishing machine ensure long service lives and less waste. Changing the process water after approx. 80 machine hours or 4 weeks is recommended. Any odours are prevented and the service life extended by adding an additional 1% of the compound. Protects employees, the environment and makes storage simpler by doing away with corrosive ingredients.

- **Universally suitable for all ferrous metals and NSF-certified.**
- **It boosts the grinding performance and effectively cleans workpieces and grinding bodies.**
- **Corrosion protection ensures safety.**

Application:

Only add the compound to the process water in the water tank in the specified dose. The measuring jug supplied with the vibratory finishing machine facilitates correct dosing. Also very well suited for use in our GARANT vibratory finishing machine GMT2 (No. 501310 GMT2).

Technical description

Data sheet

pH value	7.6 %
Dosage	5 - 7 %
Series	GreenPlus
Sustainability	GARANT GreenPlus
Contents	5 l
Product name attribute	Grinding and polishing
Type of product	Treatment agent

User data

	Suitability	V _c	ISO code
Alu Mg	suitable only under restricted conditions		
Steel < 900 N/mm ²	suitable		
Steel < 1400 N/mm ²	suitable		
Steel < 55 HRC	suitable		
Steel < 60 HRC	suitable		
Steel < 67 HRC	suitable		
Carbide (HM)	suitable		
INOX	suitable		
Ti	suitable		
GG(G)	suitable		
CuZn	suitable only under restricted conditions		
Uni	suitable		
wet maximum	suitable		