

**Torque screwdriver, fixed setting, without scale, set torque: 0,9N·m****Order data**

Order number	659890 0,9
GTIN	4069515041744
Item class	62E

**Description****Version:**

Torque screwdriver with easy-grip 2-component handle and **fixed torque**. When the set torque is reached the screwdriver triggers, with clearly audible and perceptible signals. Suitable for clockwise tightening. **It is not possible to tighten the screw any further.**

**Advantage:**

Torque screwdriver can be used with all conventional bits C 6.3 and E 6.3 (similar to No. 675155, 675390).

**Application:**

For controlled tightening of screws to a pre-set torque.  
Ideal for fitting indexable inserts.

**Standard:**

Tested to **DIN EN ISO 6789**.

**Accuracy:**

±10% of the specified value.

**Note:**

All Wiha interchangeable blades (No. 659940 – 659946) can also be used in the HOLEX torque screwdriver No. 659945.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

The set torque value **cannot** be changed.

**Technical description**

Data can be recorded	no
Setting the trigger value	preset

## Data sheet

Overall length L	168 mm
Bit socket	D 6.3
Bit socket	F 6.3
Adjustable trigger value	non-adjustable
Measurement technology	mechanical
Display	analogue
Measurement process	Torque
Standard	DIN EN ISO 6789
Calibration	O1
Release signalling	acoustic
Release signalling	haptic
Trigger principle	mechanical slip clutch
Direction of tightening	Right-hand tightening
set torque	0.9 Nm
set torque	90 cNm
Connection format	Bit holder 1/4 inch
Torque measuring accuracy	±10 %
Feedback	acoustic signal
Feedback	triggering
Torque fixed setting	yes
Type of product	Torque screwdriver

### Suitable products

No Shop URL available for: 659890 0,9