# Garant

# GARANT Uni Hero solid carbide drill, plain shank DIN 6535 HA, TiAlSiN, Ø DC h7: 13mm



#### **Order data**

Order number	GG1255 13
GTIN	4067263106562
Item class	GGN

### **Description**

#### **Version:**

The ultimate in universality and profitability in one tool. Robust tool design and convex-concave curved cutting edge design for optimum tool stability and chip breakage behaviour in a wide range of materials. Special flute geometry and polished flutes for ideal chip evacuation and maximum process reliability. Ultra-smooth TiAlSiN high-performance coating to effectively reduce wear and the formation of built-up edges.

Same as number: 123020.

Form HB available with No. GG1258 at the same price.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Articles with prices in brackets: Different delivery time and minimum order quantity is 3 pieces.

### **Technical description**

Overall length L	178 mm	
Standard	Manufacturer's standard	
Tolerance nominal Ø	h7	

## Data sheet

Contents	5″	
Nominal Ø D <sub>c</sub>	13 mm	
Shank Ø D <sub>s</sub>	14 mm	
recommended maximum drilling depth $L_2$	113.5 mm	
Number of cutting edges Z	2	
Flute length $L_c$	133 mm	
Feed f in steel < 1100 N/mm <sup>2</sup>	0.23 mm/rev.	
Coating	TiAlSiN	
Tool material	Solid carbide	
Version	8×D	
Point angle	140 degrees	
Shank	DIN 6535 HA to h6	
Through-coolant	yes, with 25 bar	
Machining strategy	HPC	
Semi-Standard	yes	
Colour ring	orange	
Type of product	Jobber drill	

### **User data**

	Suitability	$\mathbf{V}_{c}$	ISO code
Alu plastics	suitable only under restricted conditions	140 m/min	N
Aluminium (short chipping)	suitable	150 m/min	N
Steel < 500 N/mm <sup>2</sup>	suitable	120 m/min	Р
Steel < 750 N/mm <sup>2</sup>	suitable	115 m/min	Р
Steel < 900 N/mm <sup>2</sup>	suitable	110 m/min	Р
Steel < 1100 N/mm <sup>2</sup>	suitable	80 m/min	Р
Steel < 1400 N/mm <sup>2</sup>	suitable	70 m/min	Р

# Data sheet

INOX < 900 N/mm <sup>2</sup>	suitable	65 m/min	M
INOX > 900 N/mm <sup>2</sup>	suitable	60 m/min	М
Ti > 850 N/mm <sup>2</sup>	suitable	35 m/min	S
GG(G)	suitable	95 m/min	K
Uni	suitable		
wet maximum	suitable		
wet minimum	suitable		
Air	suitable only under restricted conditions		
	restricted corrations		

**Suitable products** 

No Shop URL available for: GG1255 13