# Garant

# Shrink-fit chuck with cooling channel bore, HSK-A 63 ultra short, Clamping range $\varnothing$ D1: 20mm



### Order data

Order number	308165 20
GTIN	4045197468697
Item class	31A

## **Description**

#### **Version:**

From clamping  $\emptyset$  D<sub>1</sub> 6 mm with tapped holes for balancing screws.

- · High-temperature steel.
- · Sizes 3 5 for carbide, from size 6 for HSS and carbide.
- · With RFID/Balluffchip bore.

GARANT: HSK mating faces machined. All shanks hard turned (for smooth running!).

**Ultra short:** More stability and stiffness, less vibration. This ensures longer tool life and better surface quality. No length adjustment available.

With **cooling channel bores** tapped for plugging.

# **Application:**

- · For holding end mills and drills with parallel shank to h6 tolerance.
- · Suitable for inductive, contact and hot air shrink-fit units.

#### **Supplied with:**

For chucks with length adjustment including a length adjustment screw (from clamping  $\varnothing$  D<sub>1</sub> 6 mm).

### **Optional extras:**

Coolant tube No. 309880, socket wrench No. 309890, shrink-fit chuck extension No. 302410 – 302416, shrink-fit units No. 354210 – 354450, balancing screw set No. 309906 180.

## **Technical description**

$\emptyset D_2$	35 mm
Clamping Ø D <sub>1</sub>	20 mm
Overhang dimension A	75 mm
External Ø D	43 mm
Cooling channel bore	lockable
Adapter	HSK-A 63 ultra short
Arbor standard	DIN 69893
Arbor standard	ISO 12164-1
Shape	A
Balance quality G at rotational speed	G 2.5 at 25,000 rpm
Concentricity	≤ 3 µm
Machining strategy	HPC
Machining strategy	HSC
Type of product	Shrink-fit chuck

# **Accessories**

Cooling unit Type CU1	354215 CU1
Subframe cupboard	354290
Screening plate for coilSU1 for clamping Ø 12-20 mm	354240 12-20
Cooling adapter short 4.5° for clamping Ø 16,1-22 mm	354235 16,1-22
Shrink-fit unit Type SU1	354210 SU1
Screening plate for coilSU1 for clamping Ø 20-32 mm	354240 20-32
Cooling adapter long4.5° for clamping Ø 16,1-22 mm	354236 16,1-22